

AFTER A POOL LINER CHANGE

NEXT STEPS FOR REINSTALLING YOUR INGROUND POOL LIGHTING SYSTEM GLASSES AND RINGS

If the installation of your new pool liner is complete, it is now time to plan for the reinstallation of the glasses and rings so that you can once again enjoy bright evenings with your family!

PRIOR TO THE APPOINTMENT

MAKE SURE YOUR POOL IS FILLED TO CAPACITY AND THAT THE FOLLOWING TASKS ARE COMPLETED:

You must **keep the light niches clean.** Remove sand, dirt, rocks, and any possible water accumulation. In fact, it is **strongly recommended to do this maintenance every year** (see back page for more information)!

Also check to see if the lighting system you have

is working properly and if any parts need to be replaced. Please notify the call centre agent if there is any verification that needs to be done other than the tasks listed in the contract with your pool company.

The technician's job is to **reinstall the glasses and rings.** He will not perform cleaning maintenance for you. If the niches are too dirty to do the work and he has to reschedule an appointment with you, **you may be charged an additional fee.**

Is your lighting system outdated?

Do you think it needs a retrofit? It is possible to install a new LED system in colour or white. You will find all the details on our website www.lumi-o.com or you can ask your local store's representative.

Once our technician has completed the reinstallation of the glasses and rings, you will be able to enjoy it right away, brighten up your yard and evenings!

Having any questions? Visit our website www.lumi-o.com/FAQ Or contact us by phone or email:

1-800-363-2396 / callcenter@lumi-o.com

Thank you for supporting a Canadian product!

Did you know that Lumi-O | InnovaPlas is in business since 1982?

REQUIRED TOOL:

Wet/Dry Vacuum Cleaner (like a 4 HP or 6 HP Shop-Vac)





PROCEDURE LED LIGHT WINTERIZATION

- Open the round cover on the sidewalk *For in-ground pool only*;
- 2 Loosen the 3 butterfly screws around the light (DO NOT REMOVE THEM);
- **3 Hold the light** and **turn it** a quarter of a turn;
- 4 Unhook the light from the ring and pull it out onto the sidewalk;
- 5 Follow the wire to the "Quick-Plug" and unscrew the black bolt;
- 6 Separate the wires (male and female);
- 7 The female wire must remain in place in the junction box and it is recommended using grease (e.g. Vaseline) to avoid corrosion;
- 8 Store the light in a warm, dry place if possible.

PROCEDURE CONVENTIONAL LIGHTING WINTERIZATION

- Open the round cover on the sidewalk *For in-ground pool only*;
- 2 Loosen the butterfly screw under the light (DO NOT REMOVE IT);
- **3 Hold the light** and turn it a quarter of a turn to unhook it from the ring;
- 4 Remove the bulb and store it in a dry, warm place if possible;
- 5 To prevent the formation of verdigris and rust, **apply petroleum jelly** (Vaseline or white grease) in the socket;
- 6 Place the lamp (shell) in a plastic bag with the opening facing down in the bottom of the housing, or on the ground for an above ground pool if the wire is long enough. Otherwise, you must hang it up on the ring.

WARRANTY

POOL LINER CHANGE WARRANTY AND SERVICE CALL - IN-GROUND OR ABOVE GROUND: 1 year parts and labour

RETROFIT WARRANTY

IN-GROUND

- LED LIGTH 3 years
- Remote control, transformer and installation 1 year

RETROFIT WARRANTY ABOVE GROUND

- LED LIGHT 2 years
- Remote control, transformer and installation 1 year

Having any questions? Visit our website www.lumi-o.com/FAQ Or contact us by phone or email:

1-800-363-2396 / callcenter@lumi-o.com





